



Portable multi-channel thermocouple data logger, supports up to 16 channels thermocouple signal input. The collected data information can be displayed vividly through digital interface, bar chart interface, real-time curve and other forms. The device has rich peripheral interfaces such as USB, micro SD card and RJ45 (ethernet). It is a portable recording instrument with rich functions, high integration and intelligence.

Features

1. Support multi channel input and up to 16 channel thermocouple input.
2. Support multiple types of Thermocouple Input: K / J / E / T / R / S / N / B / C ; Wide temperature detection range : -270 ~ 2320 °C.
3. The fastest sampling frequency can reach 1s.
4. It has the function of viewing real time data curve and historical data curve.
5. Large data storage capacity. Single record capacity: 100000 records ; Total data recording capacity: 8 million records
6. A variety of external interfaces, support U disk and SD card to export the historical data, meet various needs of users.
7. Support USB flash disk and SD card to upgrade the program, which is convenient for users.



Applications



Factory



Workshop



Labs




Warehouse

Portable Multi- Channel Thermocouple Data Logger

OM-TCS1500-16



 Temperature range 270~2320°C	 Intelligent cloud platform	 1s sampling and recording	 Patented Product
 5 inch touch color screen	 Convenient touch screen operation	 Large storage space	
 USB interface	 Intelligent display function	 Support external SD card expansion	

Product informations	
Dimensions	189.3 x 103.5 x 39mm (with protective sleeve)
Display	5" capacitive touch screen, resolution 800 x 480px
Number of channels	16-channel thermocouple input
Storage capacity	Single record capacity: 100000 records ; Total data recording capacity: 8 million records
Internal storage	32GB
External transfer	Support USB flash disk (USB 2.0), micro SD card (up to 32GB)
Ethernet	Transmission rate: 10/100M bit/s , full duplex and half duplex
Battery capacity	5000mAh
Sampling frequency	1s at fast
Recording frequency	1s at fast
Data format	CSV file format
Working temperature	-10 to 50°C
Storage temperature	-20 to 60°C
Relative humidity	5% to 95% RH, non condensation
Shell material	PC + ABS plastic, protective sleeve is made from silicone



Thermocouple input (excluding cold junction error), accuracy does not include cold junction compensation error, cold junction compensation error: $\pm 1.5^{\circ}\text{C}$

Type	Measuring range ($^{\circ}\text{C}$)	Resolution($^{\circ}\text{C}$)	Maximum allowable error ($^{\circ}\text{C}$)
K	-270 - 1370 $^{\circ}\text{C}$	0.01 $^{\circ}\text{C}$	$\pm 0.5^{\circ}\text{C}$
J	-200 - 760 $^{\circ}\text{C}$	0.01 $^{\circ}\text{C}$	$\pm 0.5^{\circ}\text{C}$
E	-270 - 980 $^{\circ}\text{C}$	0.01 $^{\circ}\text{C}$	$\pm 0.5^{\circ}\text{C}$
T	-270 - 400 $^{\circ}\text{C}$	0.01 $^{\circ}\text{C}$	$\pm 0.5^{\circ}\text{C}$
R	-50 - 1760 $^{\circ}\text{C}$	0.01 $^{\circ}\text{C}$	$\pm 2^{\circ}\text{C}$
S	-50 - 1760 $^{\circ}\text{C}$	0.01 $^{\circ}\text{C}$	$\pm 2^{\circ}\text{C}$
N	-270 - 1300 $^{\circ}\text{C}$	0.01 $^{\circ}\text{C}$	$\pm 2^{\circ}\text{C}$
B	600 - 1820 $^{\circ}\text{C}$	0.01 $^{\circ}\text{C}$	$\pm 2^{\circ}\text{C}(600\sim 1820)$
C	0 - 2320 $^{\circ}\text{C}$	0.01 $^{\circ}\text{C}$	425 $^{\circ}\text{C}$: $\pm 4.5^{\circ}\text{C}$, 425-2320 $^{\circ}\text{C}$: 1.0%

